

Common vision of cooperation WP3 Output 3.2

dr. Mojca Šraj, dr. Mira Kobold, dr. Sašo Petan,

dr. Nejc Bezak, dr. Philipp Liedl, dr. Mitja Brilly

University of Ljubljana, Faculty of Civil and Geodetic Engineering, Slovenia STASA - Steinbeis Angewandte Systemanalyse GmbH, Germany

Ljubljana, 30. 10. 2020



Contents

1		Intro	duct	ion	3
2		Revie	ew o	f the forecasting conditions	3
	2.1	L	Mor	nitoring and data	3
		2.1.1	•	Meteorological data	4
		2.1.2		Hydrological data	6
		2.1.3	,	Ice data	9
	2.2	2	Hyd	rological forecasting methods and models	10
3		Analy	ysis (of the information flow among neighbouring countries	15
4		Bottl	ene	ck analysis of the update frequencies for real time hydrological and meteorological	
ex	cha	ange	of d	ata	18
5		Reco	mm	endations for improvement	24
	5.1	L Rec	omn	nendations related to meteorological and hydrological monitoring and data	24
		5.1.1	. Me	teorological data	24
		5.1.2	! •	Hydrological and ice data	25
	5.2	2	Reco	ommendations related to hydrological forecasting methods and models	26
	5.3	3	Reco	ommendations related to data exchange and IT-infrastructures	28
6		Refe	renc	es	30



1 Introduction

Frequency of floods in the Danube River Basin increased in the last decades (e.g. major floods in 2002, 2005, 2006, 2009, 2010, 2013, and 2014), urging the need for a more effective and harmonized regional and cross-border cooperation in the field of flood and ice forecasting. Flood forecasting is one of the most effective flood risk mitigation measures serving to protect human lives and social estate, however, the quality of hydrological forecast depends on several factors like the accuracy of meteorological forecast, the quantity and quality of meteorological and hydrological data, data exchange, organizational structure of national hydrological and meteorological services, etc.

The main aim of the DAREFFORT (Danube River Basin Enhanced Flood Forecasting Cooperation) project is to give a comprehensive overview about the complex national flood and ice forecasting systems and to eliminate the shortcomings of the existing forecasting practices as well as to improve the exchange and availability of hydrological and meteorological data between the participating countries with establishment of the Danube Hydrological Information System (Danube HIS). Based on the Activity 3.1 (Output 3.1 and corresponding Deliverables) as well as on the Report on elaboration of the forecasting conditions (Deliverable 3.2.1) and identified gaps and bottlenecks (Deliverable 3.2.4) recommendations for improvement of the flood and ice forecasting systems (Deliverable 3.2.3) were prepared in order to achieve the aforementioned goals.

2 Review of the forecasting conditions

Enhancement of the conditions of hydrological forecasting generally depends on improving the quantity and quality of several types of data: meteorological and hydrological data, ice data, channel morphology etc. and accuracy of meteorological forecasts. Hydrological and meteorological services maintain monitoring systems and development of weather and hydrological forecasting models. Improvements in meteorological forecasts have an impact on improving hydrological forecasts. The organizational structure of hydrological and meteorological services by countries of the Danube River Basin is different as shown in Evaluation report on flood and ice forecasting systems and methodologies in the Danube countries (WP3 output 3.1). Increased flood risk in the Danube River Basin should be directed to the improvement of forecasting capabilities on basin-wide scale.

2.1 Monitoring and data

In-situ monitoring of meteorological and hydrological variables from data providers are particularly crucial for reliable hydrological forecast. Additionally, reliable data flow, data control and data processing are extremely important for efficient data management. Countries use different transmission techniques in data flow and different software for data control and data processing. The improvement of forecasting capabilities on basin-wide scale is the most cost-effective non-structural tangible solution, which highly reflects the solidarity principle. Therefore, the strong cooperation between countries in the region is necessary.



2.1.1 Meteorological data

Meteorological observations are an essential part of flood and ice warning and forecasting system. Generally, within the meteorological networks various data is collected. The most important variables are precipitation, air temperature, air humidity, wind speed, air pressure, solar radiation, sunshine duration, evaporation, soil moisture, snow depth and snow water equivalent.

We have to emphasize that actual measurements of evaporation and transpiration are performed only in some countries at few meteorological stations. Furthermore, potential evaporation is measured only at some places (see Evaluation report on flood and ice forecasting systems and methodologies in the Danube countries (WP3 output 3.1)). In addition, soil moisture measurements are hardly taken. Furthermore, composite weather radar imagery to be used in hydrological models are not available in all countries.

The floods in the Danube river basin are mainly generated in mountainous areas in combination with snowmelt. In most countries, there are no systematic measurements of snow water equivalent or its spatial distribution.

The availability and access to data is different across the Danube River Basin countries. Furthermore, not all of the data are free of charge in individual countries. Availability of meteorological data, terms of use for the countries involved in the DAREFFORT project and the number of on-line meteorological stations operated in the Danube River basin is shown in Table 1 and information about the type of data provided on the public website is presented in Table 2.

Table 1: Availability of meteorological data and terms of use in individual countries and the number of on-line meteorological stations operated in the Danube River basin (DRB) (information from national reports)

Country	Data availability and access	Terms of use	No. of on- line meteorologi cal stations operated in DRB
Austria	www.ehyd.gv.at	All data is free of charge and can be used for research purposes as well for commercial purposes. Reference to the data source is required.	NA
Bulgaria	www.meteo.bg	Data access is limited and use of data is not free of charge.	116
Croatia	http://www.meteo.hr/	Archive data is not charged for scientific research use whereas for commercial use a fee is charged according to the price list of services and products.	12



Country	Data availability and access	Terms of use	No. of on- line meteorologi cal stations operated in DRB
The Czech Republic	www.chmi.cz	Operational data is available for public on the CHMI website. Verified data are not available on the website and only provided as a paid service.	90
Germany	https://m.hnd.bayern.de/ https://www.gkd.bayern.de/ https://opendata.dwd.de	The DWD does not give any guarantees for availability and service for its open data service. If a high level of data integrity and continuity is required there is a secured access in the so-called Geodata Service (Geodaten-Serverdienst). The use of this service is fee-based and serves the same data as the Open Data Service.	414
Hungary	www.met.hu	The data is provided for a fee, but basic data is free of charge.	appr. 300
Moldova	http://old.meteo.md/ http://www.meteo.md/index.php/me teo/	NA	6
Romania	http://www.meteoromania.ro/	NA	160
Serbia	http://www.hidmet.gov.rs/	The data that is published on the web site, both in real time and yearbooks, as well as the data provided to state institutions, are free of charge. Data issued on request are charged.	28
Slovakia	http://www.shmu.sk/	To the bodies of state and public administration, to the court and the National Council of the Slovak Republic, the data is provided free of charge for exercise of their powers. In other cases, meteorological products are provided for remuneration.	271
Slovenia	http://meteo.arso.gov.si/met/en/	All the data are free of charge and can be used for research purposes as well for commercial purposes. A source of data is required.	113
Ukraine	https://meteo.gov.ua/	Data is provided to government agencies free of charge. In other cases, the data is charged.	0

NA indicates that this information is not available (not provided in the country reports)



Table 2: Information about the type of data provided on the public website (from national reports)

Country /			Type of data provi	ided on the	e public w	ebsite	
Region	(air	temp., humic	lity, precipitation,	precip. typ	e, snow co	over, air qualit	y, other)
Austria	air temp.	humidity	precipitation				
(Lower							
Austria)							
Bulgaria			precipitation	precip.	snow		
				type	cover		
Croatia	air temp.	humidity	precipitation		snow		
					cover		
Czech	air temp.	humidity	precipitation		snow	air quality	
Republic					cover		
Germany	air temp.	humidity	precipitation		snow		wind, global
					cover		radiation, air
							pressure
Hungary	air temp.	humidity	precipitation	precip.	snow	air quality	wind
				type	cover		
Moldova	air temp.	humidity	precipitation		snow	air quality	air pressure,
					cover		wind speed,
							wind direct.
Serbia	air temp.	humidity	precipitation		snow		
					cover		
Slovakia	air temp.	humidity	precipitation		snow	air quality	air pressure,
					cover		wind speed,
							wind direct.
Slovenia	air temp.	humidity	precipitation	precip.	snow		
				type	cover		
Ukraine	air temp.		precipitation	precip.	snow		
				type	cover		

2.1.2 Hydrological data

In the frame of hydrological monitoring all countries collect data on hydrological parameters, i.e. water level, discharge and water temperature. Some of them collect also information about sediments and ice and there are practically no systematic measurements of water flow velocity. Bed load transport is hardly ever measured. There are also no systematic measurements of channel morphology, with the exception of navigable waterways along the Danube and its tributaries.

Measurements of river stages, and indirectly river discharges, are well developed in all hydrological services. However, the number of observation stations has unfortunately decreased over recent decades and we lost valuable information regarding the heterogeneity and dynamics of the phenomena measured. Furthermore, digitalisation of historical data is lacking in all services.

The problem of hydrological as well as meteorological services is also the lack of financing and frequently reduced allocations of budgetary resources of individual countries. Consequently, the number of gauging stations in some countries is lower than several decades ago. Thus, the reduction of funds for operation of hydrological as well as meteorological services have forced the services to



improve their budgets by selling data. This fact however could bring more harm than benefits for the society. The lack of funds makes it difficult to introduce new measurement technologies. In some countries, digitisation and automation have been introduced into all observations and in others only partially.

The availability and access to hydrological data is different across the Danube River Basin countries. Furthermore, not all of the data are free of charge in individual countries. Availability of hydrological data and terms of use for the countries involved in the DAREFFORT project is shown in Table 3 and the type of the data provided on the public website in Table 4.

Table 3: Availability of hydrological data, terms of use in individual countries and the number of automatic online hydrological stations operated in Danube River Basin (DRB)

Country	Data availability and access	Terms of use	No. of on-line hydrological stations operated in DRB
Austria	www.ehyd.gv.at	All data is free of charge and can be used for research purposes as well for commercial purposes. Reference to the data source is required.	NA
Bulgaria	www.hydro.bg	The access to the data is limited. The use of data is not free of charge.	25
Croatia	http://hidro.dhz.hr	Archive data are not charged for scientific research use whereas for commercial use a fee is charged according to the price list of services and products.	172
The Czech Republic	http://hydro.chmi.cz/hpps/	Verified hydrological data (time series, daily averages, monthly averages etc.) is charged and available upon request.	153
Germany	https://hnd.bayern.de/ https://www.gkd.bayern.de/	Data for water levels, discharge, water temperature and sediments can be requested for single stations.	488
Hungary	www.vizugy.hu www.hydroinfo.hu	Data can be provided for a certain fee or free of charge.	350
Moldova	http://www.meteo.md/index .php/hidrologie/	Hydrological data and forecasts for representative stations are public available.	12
Romania	http://www.inhga.ro/ http://www.rowater.ro/	Hydrological data and forecasts for representative stations on the Danube and national rivers are public available, on the daily national reports elaborated by the National Hydrological Forecast Centre.	NA
Serbia	http://www.hidmet.gov.rs/	Data published on the web site, both in real time and yearbooks, as well as the data provided to state institutions, is free of charge. Data issued on request is charged.	96



Country	Data availability and access	Terms of use	No. of on-line hydrological stations operated in DRB
Slovakia	http://www.shmu.sk/	To the bodies of state and public administration, to the court and the National Council of the Slovak Republic, data is provided free of charge for exercise of their powers. In other cases, hydrological products are provided for remuneration.	306
Slovenia	http://www.arso.gov.si/vode/podatki/	All data is free of charge and can be used for research purposes as well for commercial purposes. Reference to the data source is required.	139
Ukraine	https://meteo.gov.ua/	The data is provided free of charge to government authorities. In other cases, hydrological data is charged.	2

Information from national reports

NA indicates that this information is not available (not provided in the country reports)

Table 4: Information about the type of data provided on the public website (from national reports)

Country / Region	Type of the data provided on the public website							
	(water level, discharge, water temperature, water quality,							
		sediment transport, ice cover)						
Austria (Lower Austria)	water	discharge	water					
	level		temperature					
Bosnia and Herzegovina	water							
	level							
Bulgaria	water	discharge						
	level							
Croatia	water	discharge						
	level							
Czech Republic	water	discharge	water					
	level		temperature					
Germany	water	discharge	water	water	sediment			
	level		temperature	quality	transport			
Hungary	water	discharge	water			ice		
	level		temperature			cover		
Moldova	water	discharge				ice		
	level					cover		
Romania	water	discharge				ice		
	level					cover		
Serbia	water	discharge	water			ice		
	level		temperature			cover		
Slovakia	water	discharge	water			ice		
	level		temperature			cover		



Country / Region	Type of the data provided on the public website (water level, discharge, water temperature, water quality,					
	sediment transport, ice cover)					
Slovenia	water	discharge	water		sediment	
	level		temperature		transport	
Ukraine	water		water			
	level		temperature			

2.1.3 Ice data

Ice measurements are conducted along the Danube River's main flow and its navigable tributaries, based on the recommendation adopted by the Danube Commission. In other water bodies there are some ice measurements or observations. Because of the frequent problems with ice and historical floods, these services are best organised in Hungary. A review of the problems related to ice on the Danube is provided in the report "Die Donau und ihr Einzugsgebiet - Eine hydrologische Monographie, Folgeband II, Temperatur- und Eisregime der Donau und ihrer wichtigeren Zubringer", published in 1993 (IHP UNESCO, 1993). Furthermore, the ICPDR has published an ice report entitled "Report on the ice event 2017 in the Danube River Basin", compiled by its Flood Protection Expert Group (FP EG), which contains a comprehensive overview of ice features, past ice events on the Danube, lessons learnt and recommendations for the future (ICPDR, 2018).

In hilly headwater parts of the basin the ice build-up in the channel does not cause significant back water effect or particular problems during floods. Ice events are dangerous because in combination with increase of river flow due snowmelt or rainfall can cause catastrophic floods. Currently, the combinations of extremely rare events the so-called compound events, such as ice and rainfall, snow cover and rainfall, are not covered adequately enough by hydrological models or forecasting protocols.

Table 5: Information about ice data in individual countries (from national reports)

Country / Region	lce events	Information provided concerning ice events (% of surface covered by ice, thickness of ice cover, duration of ice cover, other)				
Austria (Lower	reports No		duration of it	duration of ice		
Austria (Lower	INO			cover		
Bosnia and Herzegovina	Yes	% of surface covered by ice				
Bulgaria	Yes				Type of ice event	
Croatia	Yes		thickness of ice cover	duration of ice cover		
Czech Republic	No			duration of ice cover		
Germany	Yes			duration of ice cover		
Hungary	Yes	% of surface covered by ice	thickness of ice cover	duration of ice cover		



Country / Region Ice		Information provided concerning ice events				
	events	(% of	surface covered by	ice, thickness of ic	e cover,	
	reports		duration of i	ce cover, other)		
Moldova	Yes		thickness of ice	duration of ice	Type of ice	
			cover	cover	event	
Romania	Yes	% of surface	thickness of ice	duration of ice		
		covered by ice	cover	cover		
Serbia	Yes	% of surface	thickness of ice	duration of ice		
		covered by ice	cover	cover		
Slovakia	Yes	% of surface			Type of ice	
		covered by ice			event	
Slovenia	No					
Ukraine	Yes	% of surface	thickness of ice	duration of ice		
		covered by ice	cover	cover		

2.2 Hydrological forecasting methods and models

The national hydrological and the meteorological forecasting services of the Danube River countries mostly operate within the same institution, on a door-to-door principle (Table 6). In such case, the hydrological services have access to the meteorological data and predictions free of charge, daily consultations with meteorologists are practice and usually both services prepare joint warning product as well. On the contrary, the hydrological services that operate separately from the meteorological service have fee-based access to the meteorological data and predictions, limited consultation options and independent warning products. Since the hydrological phenomena depend on the weather conditions, it is strongly recommended to maintain the relationship with the responsible meteorological service on a high level: the formal collaboration protocols should be continuously subjected to improvements and the meteorological products and services development followed.

Table 6: Collaboration between the national hydrological and meteorological forecasting services in different Danube River countries and organizations (Information from national reports)

Country / Region	Relation with meteo service	Consultation with meteorologists	Meteorological data and predictions availability	Joint warning products
Austria	Separated	NA	Yes, payment-based	No
Bulgaria	Door-to-door	Daily	Yes, free of charge (internal IS)	Yes
Croatia	Door-to-door	Daily	Yes, free of charge (ftp, dBase)	Yes
Czech Republic	Door-to-door	Daily	Yes, free of charge (internal IS)	Yes
Germany (Bavaria)	Separated	Contact person available	Open data service + fee-based service (ftp, web)	No
Hungary	Separated	NA	Yes, free + payment based data (ftp, dBase)	NA
Moldova	Door-to-door	NA	Yes, free of charge (dBase)	NA
Romania	Separated	Daily	Yes, free of charge (internal IS)	No
Serbia	Door-to-door	Daily	Yes, free of charge (internal IS)	Yes
Slovakia	Door-to-door	Daily	Yes, free of charge (internal IS)	No



Country / Relation with Region meteo service		Consultation with meteorologists	Meteorological data and predictions availability	Joint warning products
Slovenia	Door-to-door	Daily	Yes, free of charge (internal IS)	No
Ukraine	Door-to-door	Daily	Yes, free of charge (internal IS)	Yes

NA indicates that this information is not available (not provided in the reports)

The type and manner of hydrological forecasting are subject to regional natural conditions. In the upper and high slope river reaches, the discharges mostly depend on the local precipitation type and its intensity. In such regions, monitoring systems with as short as possible data transfer time steps are strongly advised for forecasting since the hydrological conditions are prone to rapid changes. The water levels of the lower river reaches are strongly influenced by the drainage from the upper catchments and the low slope of the river channel. Here, the hydrological conditions are maintained for longer periods. The change of hydrological conditions on lower river reaches is slower. Water levels on low slope rivers may be affected also by ice.

The hydrological forecasting processes are nowadays supported by various hydrological and hydrodynamic modelling systems that mostly rely on observed precipitation and air temperature data, gauged or remotely sensed (weather radar and satellite imagery), as well as on forecasts from various numerical weather prediction models. Tables 7 and 8 present an overview of different hydrological and hydraulic models, respectively, that are used in the Danube River basin countries and the two organizations, namely the European Flood Awareness System (EFAS) of the Copernicus Emergency Management Service and the International Sava River Basin Commission (ISRBC). One can notice large diversity among the Danube River countries in terms of hydrological and hydraulic models used and the number of models applied. Among the hydrological models, the deterministic/conceptual/lumped model type predominates over the deterministic/physically based/distributed model type. The lumped models are often used in semi-distributed manner by catchment division into subcatchments and/or elevation zones. The hydrological models used in more than one country (organisation) are listed in the first three rows of Table 7. Those are DHI NAM, HBV/HBV-light and HEC-HMS. Among the hydraulic/routing models the dynamic wave - hydraulic routing model type predominates over the hydrologic routing model type. The routing models used in more than one country (organisation) are listed in the first two rows of Table 8. Those are DHI MIKE 1D and HEC-RAS. Nevertheless, it does not mean that the mostly used hydrological or hydraulic models are recommended for general use in the Danube River basin. The choice of appropriate model/model type for application in a certain catchment is rather complex process. The recommendations about this process are given in the chapter 5.



Table 7: An overview of hydrological models used in different Danube River countries and organizations

Hydrological	Country /	Model Type
model	Organization	
DHI NAM	Austria, Bulgaria,	Lumped/semi-distributed (deterministic, conceptual)
	Croatia, Slovenia, ISRBC	
HBV/HBV-	Austria, Serbia, Slovakia,	Lumped/semi-distributed (deterministic, conceptual)
light	ISRBC	
HEC-HMS	Bulgaria, Czech,	Lumped/semi-distributed or distributed (deterministic,
	Slovakia, ISRBC	conceptual)
LISFLOOD	EFAS	Distributed (deterministic, semi-physical, semi-
		conceptual)
WFLOW	ISRBC	Distributed (deterministic, conceptual)
TOPKAPI	Bulgaria	Distributed (deterministic, physically based)
ANN	Bulgaria	Lumped (deterministic, empirical)
SWAT	Bulgaria	Semi-distributed (deterministic, physically based)
ISBA-	Bulgaria	Distributed (deterministic, physically based)
TOPMODEL		
HYDROG	Czech Republic	Lumped/semi-distributed (deterministic, conceptual)
LARSIM	Germany	Lumped/semi-distributed or distributed (deterministic,
		conceptual)
TAPI	Hungary	Lumped/semi-distributed (deterministic, conceptual)
SAC-SMA	Romania	Lumped/semi-distributed (deterministic, conceptual)
NOAH-R	Romania	Distributed (deterministic, physically based)
MANS	Serbia	Lumped (deterministic, conceptual)
Regression	Serbia	Lumped (deterministic, empirical)
models		

Table 8: Overview of hydraulic models used in different Danube River countries and organizations

Hydraulic model/routing model	Country / Organization	Model Type
DHI MIKE 1D	Austria, Bulgaria, Croatia, Slovenia, ISRBC	Hydraulic routing (dynamic wave)
HEC-RAS	Slovakia, ISRBC	Hydraulic routing (dynamic wave)
HYDROG	Czech republic	Hydrologic routing (kinematic wave)
FluxFloris	Germany	Hydraulic routing (dynamic wave)
WAVOS/SOBEK	Germany	Hydraulic routing (dynamic wave)
DLCM	Hungary	Hydrologic routing
Lag&K,	Romania	Hydrologic routing
Muskingum		
LISFLOOD	EFAS	Hydrologic routing (kinematic wave)



The hydrological and hydrodynamic modelling system uncertainty is further weighted with the uncertainty from the meteorological forecasts. Therefore, the hydrological services tend to issue descriptive forecasts rather than quantitative ones originating from the modelling systems. Thus, experienced hydrological forecasters hold a key role in the critical evaluation of the modelling system results as well as within the decision making processes of the hydrological forecasting service. However, with the advent of new technologies and the decline of the old ones, continuous capacity building of the hydrological forecasting services is strongly recommended. The list of available public websites with information about hydrological forecasts is shown in Table 9.

Table 9: Information about the availability of a public website to provide information about hydrological forecasts and URL of the website (from national reports)

Country / Region	Availability of a public website with hydrological forecasts	URL
Austria (Lower Austria)	Yes	NA
Bosnia and Herzegovina	Yes	www.rhmzrs.com
Bulgaria	Yes	http://hydro.bg/ https://arda.hydro.bg/ https://maritsa.meteo.bg/
Croatia	No	NA
Czech Republic	Yes	NA
Germany	Yes	https://www.hnd.bayern.de
Hungary	Yes	www.hydrionfo.hu www.vizugy.hu
Moldova	Yes	http://www.meteo.md/index.php/hidrologie/
Romania	Yes	www.inhga.ro
Serbia	Yes	https://www.hidmet.gov.rs
Slovakia	Yes	http://www.shmu.sk/en/?page=1&id=hydro_vod_all
Slovenia	Yes	http://www.arso.gov.si/vode/napovedi/
Ukraine	Yes	https://meteo.gov.ua/ua/
Entire Danube river basin	Yes (near real time forecasts are restricted – archived are freely available)	www.efas.eu

NA indicates that this information is not available (not provided in the questionnaire)



Forecasting accuracy assessment is systematically undertaken only by some individual services, mostly on an occasional basis only, i.e. when looking for improvements in the service's operation or when introducing new technologies, measurements, data transfer, modelling, and similar. Systematic assessments of forecasts are only performed by the European Commission's Joint Research Centre (JRC) — for its EFAS forecasts, covering EU member states and associate members. In terms of forecasting accuracy assessment, the level of confidence into flash floods forecasting and forecasting of floods in the middle and lower river reaches cannot be assessed in the same way. The reason lies in the weak reliability of meteorological forecasts, even with only 24-hour lead-time.

Table 10 summarizes the short- and the long-term plans of the forecasting services. One can see that future plans are relatively similar and forecasting services will work on model development (e.g., better calibration, enhanced model structure), gauging networks improvements (e.g., new stations, modern equipment, denser network), forecasting system development (e.g., use of additional data, use of ensemble forecasts, flash-flood forecasting improvements) and warning process improvement. Moreover, some of the forecasting services also indicated that they will work on media relations (e.g., web-page development, data access, social media such as Twitter or Facebook).

Table 10: Overview of future plans of the Danube River forecasting services based on the provided national and organizational reports (from national reports)

Country /	Future plans	
Organization		
Austria	IT system development	
Bulgaria	Hydrological forecasting process development (new early warning system, model	
	development), automatic hydrometric stations development (i.e. more stations))	
Croatia	Models development, automatic hydrometric stations development (i.e. new modern	
	stations (hydrological, meteorological, air quality, radar, oceanographic buoys,))	
Czech	Models development, widening of the forecast portfolio, flash flood forecasting	
Republic	development, medium-term forecasts for drought events, optimization of gauging network	
	(more stations, use of modern equipment)	
Germany	Use ensemble forecasts, use of supercomputer for hydrological modelling	
(Bavaria)		
Hungary	Hydrological forecasting system development (e.g., new 1D hydraulic model), ice-	
	forecasting development	
Moldova	Monitoring enhancement and forecasting development	
Romania	Flash flood forecasting and warning development, development of snow water equivalent	
	and rainfall grid data, use of ensemble forecasting, hydrological model development,	
	hydraulic model development	
Serbia	Hydrological modelling of additional catchment, hydraulic model development,	
	hydrological and meteorological gauging network development (e.g., number of stations)	
Slovakia	Forecasting system development (e.g., hydrological models development, use of	
	probabilistic models)	
Slovenia	Models development (e.g., Drava, Mura), warning process upgrade, enhanced	
	communication with general public via social media, web-page development	
Ukraine	Forecasting system development (use of ALADIN model for prediction, models	
	development), use of meteorological radars, hydrological and meteorological gauging	
	stations development	



Country / Organization	Future plans	
EFAS	Forecasting system development (e.g., use of additional data, better calibration, model development, use of grand ensemble forecast, better seasonal forecasting, better flashflood forecasting, increase of spatial resolution), improvement of forecast data access for the EFAS partners	
ISRBC	Meteorological data improvement (e.g., spatial coverage improvement, - increase temporal resolution, establish a nowcast,), hydrological models development (e.g., calibrate models for low and high flows by using observed hydro- meteorological data of sufficiently long record, improvement of the reservoir operation models with real-time data,), hydraulic model development (e.g., couple the hydraulic model to a hydrological model, calibrate the model for both high and low flows, flood mapping improvement), improvement of computational time taking into consideration also model quality	

3 Analysis of the information flow among neighbouring countries

Analysis of the information flow and exchange of the data among neighbouring countries was conducted based on the information about the data availability with respect to data exchange and improvement of forecasting conditions prepared in the frame of the project Activity 3.1 and corresponding Output and Deliverables.

As we know, along the course of the Danube River there are numerous border crossings. At these borders, it is particularly important to have a good exchange of data or even forecasts. If there is no good bilateral cooperation, this can be a bottleneck for a successful flood forecast for the entire Danube River basin. Many countries mentioned that already exchange their data via bilateral agreements.

Figure 1 indicates the border crossings, at which a flow of information should happen along the Danube and its tributaries. In the following, only the flow of information along the Danube and the main tributaries is described and illustrated. There are also further flows of information, e.g. between Ukraine and Slovakia. A comprehensive data transfer can lead to an improvement of the forecast results for each individual country.

First, the border crossings along the course of the Danube (1) is analysed. From the origin of the Danube in Baden-Wurttemberg the Danube River flows to Bavaria. From there the first border to another country, Austria, is crossed. From Austria the Danube flows further to Slovakia and along the Slovakian-Hungarian border. Flow of information between these countries is based on bilateral agreement with respect to national data policies. From Hungary, the Danube flows along the border between Croatia and Serbia. As for the countries mentioned before an exchange of information and knowledge is recommendable. The Danube from Serbia flows along the border between Serbia and Romania, then along the border between Romania and Bulgaria and finally, it meets a triangle of Romania, Moldavia and Ukraine, where an information flow is also of high importance. The countries mentioned above are all involved in the DAREFFORT project, so the project could provide a good basis for a better flow of information and national cooperation.



The border crossings of the larger tributaries of the Danube River are also shown in Figure 1, as they also have a considerable influence on the flood forecast.

The Inn (2) originates in Switzerland and continues to flow into Austria and Bavaria. The exchange of Information between Switzerland and especially between Austria and Bavaria are of high importance for the flood forecasting for the Danube River. Between Austria and Bavaria there is already a well-established exchange and flow of information regarding flood forecasting.

From Italy to Austria, from Austria to Slovenia, then along the Hungarian-Croatian border flows the Drava (3). It finally flows into the Danube in Croatia. A good flow of information should take place between these countries, which are connected by the Drava.

The Sava (4) flows from Slovenia to Croatia, then Bosnia and Herzegovina and Serbia. Information exchange between these countries is therefore also of high importance. For the Sava River there is already an established network of data exchange provided by SavaHIS.

The Morava (5) flows from the Czech Republic along the border between Austria and Slovakia.

The Tisza (6) flows from Ukraine along the border between Ukraine and Romania to Hungary, a short stretch of river on border between Slovakia and Hungary and finally to Serbia, from where it flows into the Danube.

The Prut (7) flows from Ukraine to Romania. These tributaries should also have a flow of information between the respective countries.






Figure 1: Necessary information flow along Danube River and its main tributaries



4 Bottleneck analysis of the update frequencies for real time hydrological and meteorological exchange of data

Based on the information about the update frequencies of real time hydrological and meteorological data among Danube River Basin countries (see Output 3.1), gaps and bottlenecks were identified.

Results of the analysis show that the availability of data of individual country as well as the update frequency, differs greatly between countries along the Danube River. If a downstream forecasting centre works with national data with a higher frequency than an upstream country can deliver, this will be a bottleneck in cross-country data exchange. In this case, data from the upstream country cannot be used optimally by the downstream countries. Figures 2 and 3 show the variables foreseen to be transmitted in the DanubeHIS and their update frequency.

Figure 2 presents the hydrological variables, namely water level (h), discharge (Q) and water temperature (tw), their update frequency and marked possible bottlenecks in data transfer. The upper and middle course countries Germany, Czech Republic, Austria, Slovakia, Hungary, Slovenia, Croatia and Serbia all have an update frequency of one hour or less and provide water level, discharge and water temperature data. Therefore, there should be no bottlenecks here. Romania supplies data once or twice a day, which is much rarer than the neighbouring country Serbia. Since Serbia is the upperlying country, there is no bottleneck in the data flow in this case. Romania, Serbia and Ukraine all have an update frequency of one to two times per day, and the upper stream countries provide the data in equal or higher frequency, so there are no bottlenecks in data transfer in this case. Regarding exchange of the data with Bulgaria, the problem arises, since Bulgaria does not supply any water temperature, which can lead to a major bottleneck in the data exchange. Moldova has a higher update frequency (every 15 minutes) than the surrounding countries. However, since Moldova does not use flood forecasting model (see Figure 5) there is no direct bottleneck here either. However, if Moldova want to process the data of the surrounding countries in the future, the update frequency of the surrounding countries is too low compared to their own frequency.

Regarding meteorological data and its update frequency, the bottlenecks look similar to those recognised for hydrological data (Figure 3). Germany, Czech Republic, Austria, Slovakia, Hungary, Slovenia, Croatia and Serbia all have an update frequency of one hour or less. There should be no problems with the exchange of information and data between these countries. However, individual countries provide different variables. The necessary variable needed in the frame of DAREFFORT project is precipitation (P), which is provided by all of the countries. At the border crossing between Croatia and Serbia there is a large difference between the update intervals of meteorological data. In Croatia, they are significantly higher comparing to Serbia. However, Croatia does not need data from Serbia with respect to flood forecasting, so there is no bottleneck here. Unlike hydrological data transfer, there is also no bottleneck between Bulgaria and Romania as both provide the required precipitation at the same frequency. On the other hand, Moldova has a higher update frequency of meteorological data than Ukraine and Romania. Here a bottleneck would arise, if Moldova would use a hydrological model for which they would need input variables from neighbouring countries. Ukraine



also has a slightly higher update frequency of the meteorological data than Romania, so the data frequency is too low for Ukraine and a bottleneck could appear.




Figure 2: Update intervals for hydrological stations and recognized bottlenecks in data transfer






Figure 3 Update intervals for meteorological stations and recognized bottlenecks in data transfer



The largest differences between the variables and the update frequency of the data are for ice data. These are shown in Figure 4. If there is no fixed update interval, this was described with "yes" in Figure 4. In some countries (e.g. Slovenia and Croatia) no ice data is recorded at all. In some countries ice data are recorded by an observer and in the others by automatic stations. Furthermore, the intervals vary strongly, namely from five minutes, over daily, up to only publishing the ice data in yearbooks. In addition, also measured variables vary strongly. All these differences can be a bottleneck for predictions of ice conditions.

The density of measuring stations and the frequency of data updates is crucial for the improvement of forecasting systems and the data exchange in the future. In general, it can be stated that a high temporal and spatial measurement density in the catchment area is important for a good flood forecast. This applies not only to the measurements in the country under consideration, but also to the upper reaches. Therefore, a high measuring frequency and a high station density is important to avoid bottlenecks.

Analysis demonstrates that currently the countries use very different hydrological and hydraulic models, which are presented in Figure 5. If a Danube-wide forecast is desired in the future, the measured variables of all of the Danube River countries are needed in a high frequency and density. An alternative way would be to exchange forecasting results. The forecast data of the border regions could then be passed on to the next country as an input data. However, in some countries, there are separate models for individual river basins and in the others, only one model for the entire country is available. However, some of the countries, such as Austria, Slovenia and Croatia, already use similar hydrological and hydraulic models. In order to make a common hydrological forecast for the entire Danube River basin possible, this would have to be further coordinated and expanded.






Figure 4: Update intervals of ice data at hydrological stations. "Yes" indicates there is no fixed update interval.






Figure 5: Forecast models used in individual countries



5 Recommendations for improvement

5.1 Recommendations related to meteorological and hydrological monitoring and data

Reliable hydrological forecast depends in a great extent on the quantity and quality of the measured meteorological and hydrological variables, which are part of the national monitoring systems of individual countries. It should be mentioned that DAREFFORT project partners are from 12 out of 19 countries covering almost the whole Danube region. However, also data from non-participating countries are needed (e.g. data from Bosnia and Herzegovina are very important for the Sava River Basin). Therefore, we also try to include non-participating countries in some of the DAREFFORT project activities, e.g. Bosnia and Herzegovina supported the project by completing the questionnaire, which was part of the Output 3.1.

Furthermore, reliable data control and data processing as well as an effective data flow are extremely important for efficient data management and therewith also for hydrological forecast.

Despite the fact that most countries in the Danube River Basin have made a significant progress in the modernization of the meteorological and hydrological measuring networks and that the modernized networks provide high quality data for forecasting models and warning procedures, there is still room for improvements.

In order to eliminate the shortcomings of the existing forecasting practices as well as to improve the exchange and availability of hydrological and meteorological data among the countries in the Danube River Basin recommendations for improvement of the flood and ice forecasting systems based on Activity 3.1 (Output 3.1 and corresponding Deliverables), identified gaps and bottlenecks (Deliverable 3.2.1) as well as the Report on elaboration of the forecasting conditions (Deliverable 3.2.1) were prepared.

5.1.1 Meteorological data

Meteorological observations are an essential part of flood and ice warnings and forecasting systems. The most important variables are precipitation, air temperature, air humidity, wind speed, air pressure, solar radiation, sunshine duration, evaporation, soil moisture, snow depth and snow water equivalent. Based on the results of the Activity 3.1 (Output 3.1 and all corresponding deliverables) as well as the Report on elaboration of the forecasting conditions (Deliverable 3.2.1) prepared in the frame of DAREFFORT project, the recommendations to meteorological services are as follows:

The Danube River Basin countries should consider the need to improve the measuring network
in terms of the stations density and the inclusion of measurements of additional variables such
as evapotranspiration, soil moisture, snow water equivalent, etc. At the moment
measurements of actual evaporation and transpiration are performed only in some countries
at few meteorological stations. Furthermore, potential evaporation is measured only at some



locations (see Output 3.1). In addition, soil moisture measurements are hardly taken. In most countries, there are no systematic measurements of snow water equivalent or its spatial distribution, despite the fact that floods in the Danube River Basin are mainly generated in mountainous areas as a combination of rainfall and snowmelt.

- The Danube River Basin countries should consider the need for development of meteorological products also at regional level, e.g. development of composite weather radar outputs at regional level.
- Countries should consider providing free access to some of the meteorological data related to the national hydrological forecasting services in the Danube River Basin for their official needs.
- Collection of historical data records, digitization and storage in a database would also be beneficial, since this data is very important for water resources management and modelling, climate change assessment, flood modelling and other meteorological and hydrological analyses.
- In relation to all above recommendations, the meteorological services should consider providing strong arguments for obtaining sufficient financial, technical and human resources to operate the services.

5.1.2 Hydrological and ice data

In the frame of hydrological monitoring all countries collect data on hydrological parameters, i.e. water level, discharge and water temperature. Some of them collect also information about sediments and ice and there are practically no systematic measurements of water flow velocity. Bed load transport is hardly ever measured. There are also no systematic measurements of channel morphology, with the exception of navigable waterways along the Danube and its tributaries (see Output 3.1).

Moreover, ice measurements are conducted only along the Danube River's main flow and its navigable tributaries, based on the recommendation adopted by the Danube Commission. In the other rivers there are only some ice measurements or observations (see Output 3.1), despite the fact that ice events are dangerous because in combination with increase of river flow due snowmelt or rainfall can cause catastrophic floods.

Based on the results of the Activity 3.1 (Output 3.1 and all corresponding deliverables) as well as the Report on elaboration of the forecasting conditions (Deliverable 3.2.1) prepared in the frame of DAREFFORT project, the recommendations to hydrological services are as follows:

• The Danube River Basin countries should consider the need to improve the measuring network in terms of the stations density and the inclusion of measurements of additional variables such as bed load, periodical cross-section morphology, water velocity measurements, etc. In the last decades, the number of observation stations has unfortunately decreased and therewith the valuable information regarding the heterogeneity and dynamics of the phenomena measured is lost.



- The Danube River Basin countries should consider the need to improve the measuring network in terms of the inclusion of ice and snow measurements, since the combinations of extremely rare events the so-called compound events, such as ice and rainfall, snow cover and rainfall, are not covered adequately enough by hydrological models or forecasting protocols.
- Countries should consider providing free access to some of the hydrological data related to the national hydrological forecasting services in the Danube River Basin for their official needs.
- Development of hydrological products at regional level, e.g. hydrological bulletins of transboundary rivers, etc. Such efforts could be also supported by making use of the Danube River Basin wide outputs from EFAS.
- Collection of historical data records, digitization and storage in a database would also be beneficial, since this data is very important for water resources management and modelling, climate change assessment, flood modelling and other meteorological and hydrological analyses.
- In relation to the project scope, countries should consider standardized data exchange for sharing hydrological data. The HyMeDES Environet Data Exchange Platform developed in DAREFFORT project supports this standardized data exchange. It is highly recommended to use this platform and to establish it as a standard for hydrological data exchange within the Danube basin, e.g. in future Danube HIS.
- In relation to all above recommendations, the hydrological services should consider providing strong arguments for obtaining sufficient financial, technical and human resources to operate the services.

5.2 Recommendations related to hydrological forecasting methods and models

Since frequency of floods in Danube River Basin increased in the last decades, the need for a more effective and harmonized regional and cross-border cooperation in the field of flood forecasting is needed. The overview of the national hydrological forecasting services organizational structure prepared in the frame of DAREFFORT project (Output 3.1) demonstrates that most of the services operate in several regional offices accompanied by a central office. They are usually organized within the national hydrometeorological or water management organization as bodies of ministries from various fields (environment, agriculture, defence, inner affairs).

Based on the results of the Activity 3.1 (Output 3.1 and all corresponding deliverables) as well as the Report on elaboration of the forecasting conditions (Deliverable 3.2.1) prepared in the frame of DAREFFORT project, the recommendations for development of hydrological forecasting methods and models are as follows:

 Hydrological forecasting systems for various catchments within the Danube River Basin (micro, meso and macro scale) should be developed taking into account already existing systems at the different scales particularly the only Danube wide forecasting system EFAS and the Sava forecasting system from the ISRBC. Early establishment and capacity development of



appropriate teams for development and management of the future forecasting system is strongly recommended.

- The catchment characteristics (size, topography, land cover, river network, slope, etc.), the river flow characteristics (floodplains, reservoirs, diversions, backwater effects, etc.), the hydro-climatic conditions, the forecasting purpose and the administrative conditions and constraints (organisational capability, computational resources, data and weather forecast availability) should be taken into account while making the choice on the appropriate hydrological/hydraulic model to be used. It is strongly suggested to follow the WMO Manual on flood forecasting and warning (WMO, 2011), the guidelines of the WMO Flood forecasting initiative (Decision-Support for the Selection of Flood Forecasting Models, 2013) as well as the latest literature on flood forecasting techniques and their applications (examples: Jain et al., 2018; Kauffeldt et al., 2016; Adams and Pagano, 2016).
- Enhancement of the hydrological service relationship with the responsible meteorological service related to data exchange, consultations, joint warnings etc. It is true that the national hydrological and the meteorological forecasting services of the Danube River countries mostly operate within the same institution, on a door-to-door principle (see Output 3.1), which enables the hydrological services access to the meteorological data and predictions free of charge, daily consultations with meteorologists and preparation of joint warning product as well. However, there are some countries, where the hydrological services operate separately from the meteorological services and have fee-based access to the meteorological data and predictions, limited consultation options and independent warning products.
- Limited resources and lack of data reduce the development of hydrological models. Furthermore, it is questionable using complex models if there is no sufficient data available for their use. Additionally, individual modelling methods were developed in different climates and some processes are treated in the model in more detail than the others are. Therefore, it is recommended to further develop the existing modelling methods and to use various models in the development of hydrological forecasts (multi-model approach) as well as ensemble forecasting. Where possible, open-source models should be used and fostered to ensure transparency to the users and to make optimum use of the limited resources.
- Systematic forecasting accuracy assessment and critical evaluation of the forecast for the
 entire Danube River Basin should be developed. At the moment forecasting accuracy
 assessment is systematically undertaken only by some individual services, mostly on an
 occasional basis only. The Danube River Basin wide forecast accuracy assessment available in
 EFAS may serve as best-practice examples that can be transferred to national or regional
 systems.
- Continuous capacity building of the hydrological forecasting services is strongly recommended, since experienced hydrological forecasters hold a key role in the critical evaluation of the modelling system results as well as within the decision making processes of the hydrological forecasting service.
- Strengthening the IT support (skilled staff) and the IT capabilities (resources, tools, services) dedicated for flood forecasting in the individual forecasting services should be considered.



- Hydrological forecasting systems primarily use data from the observation network, which is
 maintained by the hydrological service. Data measured and collected by individual water users
 like hydroelectric power plants, water supply and irrigation systems and other users are not
 included in the forecast system. Therefore, it is recommended to collect all the water regime
 data in a single database, including data from private companies.
- Improvement of cooperation among the hydrological services within the Danube River Basin by organising regular expert meetings on flood forecasting.
- Establishment of regional or bilateral agreements is also strongly recommended. Platforms such as EFAS, where hydrological services from all Europe regularly exchange information and latest developments in flood forecasting represent already existing networks that can further foster the cooperation.

5.3 Recommendations related to data exchange and IT-infrastructures

The recommendations for hydrological and meteorological monitoring, and also the recommendations for improvements of hydrological forecasting described above imply that data and information exchange between countries a very important aspect to achieve the addressed improvements in flood and ice forecasting. With the HyMeDES Environet Platform a comprehensive software for exchanging measured data in a common format has been developed in the frame of DAREFFORT project, which will serve as basis for future Danube HIS. Based on the experiences in implementing the HyMeDES Environet Platform common data exchange platform and the related flood forecasting and IT expert recommendations (Deliverable D4.1.1) following recommendations for further improvements of data exchange can be derived:

- Essential for data exchange between a multitude of different institutions is to agree on a standardized way of providing the data to the users (e.g. forecasting centres, ministries, civil protection, s, etc.). It is highly recommended to use well established standards for data provision. For HyMeDES Environet Platform the OGC standard WaterML 2.0 format has been chosen to provide the common data bases for the users.
- Today national data providers of measured data, but also national forecasting centres are using very different formats for providing their data / forecasting results. Whereas those formats have been developed and improved over time in established co-operations between data providers, forecasting centres, and stakeholders mainly on a national level, it would be helpful for further data exchange purposes, e.g. for developing a common forecasting result exchange platform to harmonize also the data formats in which data providers and or forecasting centres (which would serve as data providers for forecasted data) deliver data to the data exchange platform. This would shorten the development and implementation time for such platforms. Important topics which should be standardized are:
 - Regarding international data exchange naming of variables used in the data files should be defined in English language. Also a standardizes way for naming abbreviation of variables should be used (e.g. "h" for water level, "tw" for water



- temperature, "Q" for discharge, "ta" for air temperatue, "P_total_daily" for 24h amount of precipitation).
- It is highly recommended to state the time zone of the data delivered in the data format using the UTC-standard (e.-g. UTC+1)

Regarding IT-standards following recommendations can be derived from the results of deliverable 4.1.1 (flood forecasting and IT expert recommendations) and the DAREFFORT project implementation:

- IT-standards in data delivery are mainly used by national data providers today:
 - Data delivery: FTP of Web-API are commonly used by data providers. Providing data on FTP servers is still the most common way used by national data providers to provide measured data. Nevertheless, from the perspective of modern IT-infrastructures it is recommended to use a Web-API for data provision in future implementations, because the access is more flexible, and the data itself can be served directly out of the data base using the Web-API, or even be stored in a state-of-the-art distributed storage infrastructure.
 - File-Formats: Most commonly used file formats today are CSV and XML (WaterML 2.0 is also based on XML). Whereas CSV-files are just tables which are easy to read by humans, XML format is more flexible for storing and particularly for describing the content of the file. Some countries which already implemented a Web-API like Germany serve both formats according to parameters set when calling the API. This is a solution which can be recommended for other countries planning to move towards a Web-API.
- For measured data minimum common update interval for the parameters is daily. Hydrological
 parameters recommended to be exchanged by all countries are water level, discharge and
 water temperature. Meteorological parameters recommended to be exchanged by all
 countries are precipitation and air temperature, the latter one is not provided by all countries
 today.
- An alternative way to provide meteorological real time data could be to use the GTS network (Global Telecommunication System) of WMO. WMO collects meteorological real time data within the framework of its GTS network (Global Telecommunication System). The national weather service of each country which is member of WMO sends data to WMO in the complex binary format BUFR ("Binary Universal Form for the Representation of meteorological data").
- Currently regular practice is to publish processed data (historical) once a year. Therefore, the duration of storage of the real time data should be at least one year to avoid temporary data gaps in the database as far as possible. On the other hand, real time / unprocessed data should not be available indefinitely, because of possible data incorrectness.
- Rather general recommendations for IT-data exchange platforms are the same as derived for the HyMeDES Environet Platform:
 - development of software should to be based on established coding standards and to be well commented to be easy maintainable



- o modern data exchange software should be web driven applications, light-weight, and easy to implement and to maintain,
- to make the system as open and platform independent as possible the core structure it is recommended to use simple and proven web technology (server side: HTTPS, PHP or node.js, Apache web server, Cron/Task scheduler, PostgreSQL with PostGIS extension client side: Html5, JavaScript),
- o data security: authentication should be verified using appropriate encryption methods,
- o the interaction with such platforms should be managed by Web APIs,
- it is recommended to use a plug-in-based architecture (plug-in libraries) to be able to easily add additional features
- no direct writing interaction with the underlying databases should be allowed (only access via API)

The ongoing demand for digitalization in all fields of society put an additional pressure on the development of smart information systems for citizens living or working close to rivers but also for professional stakeholders involved in flood management.

From the Evaluation of the possibilities of establishment of the international forecasting system's result exchange elaborated in the DAREFFORT project (deliverable D 3.2.2) platform it can be derived that bilateral exchange of forecasting results is already common practice in the Danube catchment and that there could be additional benefits of a Danube wide exchange platform for forecasting results. There is not a common view about the benefits of such a platform, mainly because all countries have different situations regarding their position as upstream- / downstream country and already established cross border co-operations. Nevertheless, it is recommended to work towards a Danube wide forecasting system's result exchange platform, because the harmonization of data exchange will be necessary with respect to the ongoing digitalization of society and of professional workflows in particular. Forecasted data of such a platform could also serve as a Danube wide flood forecasting information system. For such applications it is highly recommended to harmonize the flood warning systems between the countries in the Danube catchment.

With respect to smart information systems also warning apps for citizens about flood situations maybe integrated in other waring apps for catastrophes can be a helpful tool to reduce the harm of floods.

6 References

Adams, T.E., Pagano, T.C., 2016. Flood Forecasting: A Global Perspective, Flood Forecasting: A Global Perspective. https://doi.org/10.1016/C2014-0-01361-5

ICPDR, 2018. Report on the ice event 2017 in the Danube River Basin. ICPDR, Vienna, 69 p.



IHP UNESCO, 1993. Die Donau und ihr Einzugsgebiet: eine hydrologische Monographie. Temperaturund Eisregime der Donau und ihrer wichtigeren Zubringer. Volume 2. IHP National committee, 116 p.

Jain, S.K., Mani, P., Jain, S.K., Prakash, P., Singh, V.P., Tullos, D., Kumar, S., Agarwal, S.P., Dimri, A.P., 2018. A Brief review of flood forecasting techniques and their applications. International Journal of River Basin Management 16, 329–344. https://doi.org/10.1080/15715124.2017.1411920

Kauffeldt, A., Wetterhall, F., Pappenberger, F., Salamon, P., Thielen, J., 2016. Technical review of large-scale hydrological models for implementation in operational flood forecasting schemes on continental level. Environ. Model. Softw. 75, 68–76. https://doi.org/10.1016/j.envsoft.2015.09.009

WMO, 2011. Manual of flood forecasting and warning. Geneva, Switzerland.

WMO, 2013. Intercomparison of flood forecasting models. Decision-Support for the Selection of Flood Forecasting Models.